

FINDER 2026 NISAN FİYAT LİSTESİ

ÜRÜN KODU	AÇIKLAMA	DESCRIPTION	BİRİM FİYAT (EUR / Adet)	AMBALAJ (Adet)	İSKONTO GRUBU
34 Serisi Slim Röleler (6,2mm) ve 93 Serisi Soketler					
34.51.7.012.0010	Slim röle 12VAC/DC 1 kontak, 6,2mm	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
34.51.7.024.0010	Slim röle 24VAC/DC 1 CO 6A	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
93.61.7.024	Slim röle için vidalı soket	34 Series Slim Relays (6,2mm) and 93 Series Sockets	9,01	20	A
93.60.7.024	Slim röle için push-in soket	34 Series Slim Relays (6,2mm) and 93 Series Sockets	12,41	10	A
34.51.7.024.0010**	Slim röle 24VAC/DC 1 kontak, 6,2mm	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
93.61.7.024	Slim röle için vidalı soket	34 Series Slim Relays (6,2mm) and 93 Series Sockets	9,01	20	A
93.60.7.024	Slim röle için push-in soket	34 Series Slim Relays (6,2mm) and 93 Series Sockets	12,41	10	A
34.51.7.060.0010**	Slim röle (110...125V)AC/DC 1 kontak, 6,2mm	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
93.61.0.125	Slim röle için vidalı soket, (110...125V)AC/DC	34 Series Slim Relays (6,2mm) and 93 Series Sockets	14,39	20	A
93.60.0.125	Slim röle için push-in soket, (110...125V)AC/DC	34 Series Slim Relays (6,2mm) and 93 Series Sockets	14,21	10	A
93.63.3.125	Slim röle için vidalı soket, (110...125V)AC/DC, sızıtı akım önleme (44V altında bırakır)	34 Series Slim Relays (6,2mm) and 93 Series Sockets	16,42	10	A
34.51.7.060.0010**	Slim röle 230VAC 1 kontak, 6,2mm	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
93.61.8.230	Slim röle için vidalı soket, 230VAC	34 Series Slim Relays (6,2mm) and 93 Series Sockets	14,39	20	A
93.60.8.230	Slim röle için push-in soket, 230VAC	34 Series Slim Relays (6,2mm) and 93 Series Sockets	14,21	10	A
93.63.3.230	Slim röle için vidalı soket, 230VAC, sızıtı akım önleme (77V altında bırakır)	34 Series Slim Relays (6,2mm) and 93 Series Sockets	16,42	10	A
34.81.7.024.9024	Slim SSR, giriş 24VDC, çıkış 24VDC 6A 1 NO	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
93.61.7.024	Slim röle için vidalı soket	34 Series Slim Relays (6,2mm) and 93 Series Sockets	36,1	20	A
93.60.7.024	Slim röle için push-in soket	34 Series Slim Relays (6,2mm) and 93 Series Sockets	12,41	10	A
34.81.7.024.8240	Slim SSR, giriş 24VDC, çıkış 230VAC 2A 1 NO	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
93.61.7.024	Slim röle için vidalı soket	34 Series Slim Relays (6,2mm) and 93 Series Sockets	38,31	20	A
93.60.7.024	Slim röle için push-in soket	34 Series Slim Relays (6,2mm) and 93 Series Sockets	12,41	10	A
34.51.7.024.0010**	Slim timer röle 24V AC/DC, 1 kontak	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
93.68.0.024	Slim timer rölesi, 24V AC/DC, 1 CO 6A	34 Series Slim Relays (6,2mm) and 93 Series Sockets	9,01	20	A
093.16	Slim röle röprüsü, 16 yollu, mavî	34 Series Slim Relays (6,2mm) and 93 Series Sockets	43,68	10	A
093.16.0	Slim röle röprüsü, 16 yollu, siyah	34 Series Slim Relays (6,2mm) and 93 Series Sockets	4,61	10	C
093.16.1	Slim röle röprüsü, 16 yollu, kırmızı	34 Series Slim Relays (6,2mm) and 93 Series Sockets	4,61	10	C
093.60	Plastik ayırıcı plaka	34 Series Slim Relays (6,2mm) and 93 Series Sockets	1,52	10	C
093.48	Etiket plakası, 48 adet 6x12mm	34 Series Slim Relays (6,2mm) and 93 Series Sockets	12,2	1	C
060.48	Etiket plakası, 48 adet 6x12mm (CEMBRE termal taşıyıcılar)	34 Series Slim Relays (6,2mm) and 93 Series Sockets	9,37	1	C
	Not **: 24VDC/DC slim soketlere 24VDC röle takılır.	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
	Not **: 230VAC ve (110...125V)AC/DC slim soketlere 60VDC röle takılır.	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
	Not: Farklı gerilim versiyonları için bizimle iletişime geçiniz.	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
	Not: Raylı versiyonlar için bizimle iletişime geçiniz.	34 Series Slim Relays (6,2mm) and 93 Series Sockets			
41 Serisi 14mm Arayıcı Röleleri ve 93 Serisi Soketler					
41.61.9.024.0010	14mm Arayıcı röle, 24VDC, 1 kontak	41 Series 14mm Interface Relays and 93 Series Sockets			
93.02.7.024	Vidalı soket	41 Series 14mm Interface Relays and 93 Series Sockets	7,3	20	A
93.52.7.024	Vidasız (yaylı) soket	41 Series 14mm Interface Relays and 93 Series Sockets	21,02	10	A
41.61.9.110.0010**	14mm Arayıcı röle, 230VAC, 1 kontak	41 Series 14mm Interface Relays and 93 Series Sockets			
93.02.8.230	Vidalı soket	41 Series 14mm Interface Relays and 93 Series Sockets	22,81	10	A
93.52.8.230	Vidasız (yaylı) soket	41 Series 14mm Interface Relays and 93 Series Sockets	10,37	20	A
41.52.9.024.0010	24VDC, 2 kontak BA	41 Series 14mm Interface Relays and 93 Series Sockets			
93.02.7.024	Vidalı soket	41 Series 14mm Interface Relays and 93 Series Sockets	26,39	10	A
93.52.7.024	Vidasız (yaylı) soket	41 Series 14mm Interface Relays and 93 Series Sockets	26,39	10	A
41.52.9.024.0010**	24VAC/DC *, 2 kontak BA	41 Series 14mm Interface Relays and 93 Series Sockets			
93.02.0.024	Vidalı soket	41 Series 14mm Interface Relays and 93 Series Sockets	8,09	20	A
93.52.0.024	Vidasız (yaylı) soket	41 Series 14mm Interface Relays and 93 Series Sockets	21,02	10	A
41.52.9.110.0010**	230VAC **, 2 kontak BA	41 Series 14mm Interface Relays and 93 Series Sockets			
93.02.8.230	Vidalı soket	41 Series 14mm Interface Relays and 93 Series Sockets	22,81	10	A
93.52.8.230	Vidasız (yaylı) soket	41 Series 14mm Interface Relays and 93 Series Sockets	10,37	20	A
093.08	8 yollu röprüsü, 93.02 ve 93.52 soketler için, mavî	41 Series 14mm Interface Relays and 93 Series Sockets	26,39	10	A
093.08.0	8 yollu röprüsü, 93.02 ve 93.52 soketler için, siyah	41 Series 14mm Interface Relays and 93 Series Sockets	4,26	10	C
093.08.1	8 yollu röprüsü, 93.02 ve 93.52 soketler için, beyaz	41 Series 14mm Interface Relays and 93 Series Sockets	4,26	10	C
060.48	Etiket plakası, 48 adet 6x12mm (CEMBRE termal taşıyıcılar)	41 Series 14mm Interface Relays and 93 Series Sockets	12,2	1	C
	Not **: 24VAC/DC soketlere 24VDC röle takılır.	41 Series 14mm Interface Relays and 93 Series Sockets			
	Not **: 230VAC soketlere 110VDC röle takılır.	41 Series 14mm Interface Relays and 93 Series Sockets			
	Not: Farklı gerilim versiyonları için bizimle iletişime geçiniz.	41 Series 14mm Interface Relays and 93 Series Sockets			
	Not: Patlayıcı ortamlara uygun özel versiyonlar için bizimle iletişime geçiniz.	41 Series 14mm Interface Relays and 93 Series Sockets			
40 Serisi Röleler ve 95 Serisi Soketler					
40.51.9.012.0000	12VDC, 1 kontak 12A	40 Series Relays and 95 Series Sockets			
40.61.9.012.0000	12VDC, 1 kontak 16A	40 Series Relays and 95 Series Sockets	6,29	50	B
40.51.9.024.0000	24VDC, 1 kontak 12A	40 Series Relays and 95 Series Sockets	12VDC, 1 CO 12A	50	B
40.61.9.024.0000	24VDC, 1 kontak 16A, AgSnO2 kontaktı	40 Series Relays and 95 Series Sockets	24VDC, 1 CO 12A	6,29	B
40.51.8.024.0000	24VAC, 1 kontak 12A	40 Series Relays and 95 Series Sockets	24VDC, 1 CO 16A, AgSnO2 contacts	6,59	B
40.61.8.024.0000	230VAC, 1 kontak 12A	40 Series Relays and 95 Series Sockets	24VAC, 1 CO 12A	7,91	50
40.52.9.012.0000	12VDC, 2 kontak BA	40 Series Relays and 95 Series Sockets	230VAC, 1 CO 12A	12,99	50
40.52.9.024.0000	24VDC, 2 kontak BA	40 Series Relays and 95 Series Sockets	230VAC, 1 CO 16A, AgSnO2 contacts	13,27	50
40.62.9.024.0000	48VDC, 2 kontak BA	40 Series Relays and 95 Series Sockets	12VDC, 2 CO BA	7,7	50
40.52.9.110.0000	110VDC, 2 kontak BA	40 Series Relays and 95 Series Sockets	24VDC, 2 CO BA	7,7	50
40.52.024.0000	24VAC, 2 kontak BA	40 Series Relays and 95 Series Sockets	48VDC, 2 CO BA	9,5	50
40.52.8.110.0000	110VAC, 2 kontak BA	40 Series Relays and 95 Series Sockets	24VDC, 2 CO 10A	9,76	50
40.52.8.230.0000	230VAC, 2 kontak BA	40 Series Relays and 95 Series Sockets	110VDC, 2 CO BA	10,75	50
	40.51/40.52/40.61/40.62 Tip röleler için soketler	40 Series Relays and 95 Series Sockets	24VAC, 2 CO BA	9,34	50
95.05PMA	Vidalı soket 095.71 metal klips dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	40 Series Relays and 95 Series Sockets	120VAC, 2 CO BA	11,63	50
95.05PMA	Push-in soket, 095.71 metal klips dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	11,63	50
95.P5PMA	Push-in soket, 095.71 plastik tutma/ayırma klipsi dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	8,53	10
95.P5PMA	Push-in soket, 095.71 plastik tutma/ayırma klipsi dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	8,53	10
95.75PMA	Vidalı soket 095.71 metal klips dahli, 99.01 modüllerle uyumlu, (yenisi 95.05PMA'dır)	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	8,53	10
	95.05/P5 soketlerle uyumlu aksesuarlar	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	8,53	10
99.02.3.000.00	Diyet (+A1, standart polarite) (6...220V) DC	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	11,63	50
99.02.0.024.50	LED (6...24V)DC/AC	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	4,34	10
99.02.0.230.50	LED (110...240V)AC	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	4,34	10
99.02.9.024.99	LED + diyot, 6-24VDC	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	4,34	10
99.02.9.230.99	LED + diyot, 110-220VDC	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	4,34	10
99.02.0.024.98	LED + Varistör (6...24V)DC/AC	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	5,81	10
99.02.0.230.98	LED + Varistör, 110-240VAC/DC	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	5,81	10
99.02.8.230.07	Kaçak akım bypass modülü, 110-240VAC	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	4,9	10
86.30.0.024.0000	Timer, (12...24V) AC/DC, 2 Fonksiyon: On-delay, Interval, (0,05 sn...100 saat)	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	38,35	5
86.30.8.240.0000	Timer, (230...240V) AC, 2 Fonksiyon: On-delay, Interval, (0,05 sn...100 saat)	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	42,1	5
095.18	8 yollu röprüsü, 95.05 soketler için, mavî	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	3,96	10
095.18.0	8 yollu röprüsü, 95.05 soketler için, siyah	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	3,96	10
097.58	8 yollu röprüsü, 95.P5 soketler için, mavî	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	5,88	10
097.58	8 yollu röprüsü, 95.P5 soketler için, siyah	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	5,88	10
060.48	Etiket plakası, 48 adet 6x12mm (CEMBRE termal taşıyıcılar), plastik tutma/ayırma klipsileri veya etiket taşıyıcısına uygun	40 Series Relays and 95 Series Sockets	230VAC, 2 CO BA	12,37	1
	Not: Farklı gerilim versiyonları için bizimle iletişime geçiniz.	40 Series Relays and 95 Series Sockets			
	Not: Patlayıcı ortamlara uygun özel versiyonlar için bizimle iletişime geçiniz.	40 Series Relays and 95 Series Sockets			
46 Serisi Miniyatür Endüstriyel (Kısa Bacaklı) Röleler ve 97 Serisi Soketler					
46.61.9.024.0040	24VDC, 1 kontak 16A, test buton + mekanik indikatör	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.61.9.024.0074	24VDC, 1 kontak 16A, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.61.9.110.0040	110VDC, 1 kontak 16A, test buton + mekanik indikatör	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.61.9.110.0074	110VDC, 1 kontak 16A, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.61.8.024.0040	24VAC, 1 kontak 16A, test buton + mekanik indikatör	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.61.8.024.0054	24VAC, 1 kontak 16A, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.61.8.230.0040	230VAC, 1 kontak 16A, test buton + mekanik indikatör	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.61.8.230.0054	230VAC, 1 kontak 16A, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.52.9.024.0040	46.52 Tip röleler	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.52.9.024.0074	24VDC, 2 CO BA, test buton + mekanik indikatör	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.52.9.110.0040	110VDC, 2 CO BA, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.52.9.110.0074	110VDC, 2 CO BA, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.52.8.024.0040	24VAC, 2 CO BA, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.52.8.024.0054	24VAC, 2 CO BA, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.52.8.230.0040	230VAC, 2 CO BA, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.52.8.230.0054	230VAC, 2 CO BA, test buton + mekanik indikatör + LED	46 Series Miniature Industrial Relays and 97 Series Sockets			
46.61.9.024.0040	46.61 Tip röleler için soketler	46 Series Miniature Industrial Relays and 97 Series Sockets			
97.01PMA	Vidalı soket 097.71 metal klips dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	46 Series Miniature Industrial Relays and 97 Series Sockets			
97.01PMA	Vidalı soket 097.01 plastik tutma/ayırma klipsi dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	46 Series Miniature Industrial Relays and 97 Series Sockets			
97.15PMA	Push-in soket, 097.71 metal klips dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	46 Series Miniature Industrial Relays and 97 Series Sockets			
97.15PMA	Push-in soket, 097.01 plastik tutma/ayırma klipsi dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	46 Series Miniature Industrial Relays and 97 Series Sockets			
97.02PMA	Vidalı soket 097.01 plastik tutma/ayırma klipsi dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	46 Series Miniature Industrial Relays and 97 Series Sockets			
97.15PMA	Push-in soket, 097.71 metal klips dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	46 Series Miniature Industrial Relays and 97 Series Sockets			
97.15PMA	Push-in soket, 097.01 plastik tutma/ayırma klipsi dahli, 99.02 modüllerle uyumlu, 86.30 timer takılabilir	46 Series Miniature Industrial Relays and 97 Series Sockets			
095.18	8 yollu röprüsü, 97.01 ve 97.02 soketler için, mavî	46 Series Miniature Industrial Relays and 97 Series Sockets			
095.18.0	8 yollu röprüsü, 97.01 ve 97.02 soketler için, siyah	46 Series Miniature Industrial Relays and 97 Series Sockets			
097.58	8 yollu röprüsü, 97.P5 ve 97.P2 soketler için, mavî	46 Series Miniature Industrial Relays and 97 Series Sockets			
097.58	8 yollu röprüsü, 97.P5 ve 97.P2 soketler için, siyah	46 Series Miniature Industrial Relays and 97 Series Sockets			
097.00	Etiket taşıyıcı, 060.48 etiketler için, mavî	46 Series Miniature Industrial Relays and 97 Series Sockets			
097.00	Etiket taşıyıcı, 060.48 etiketler için, siyah	46 Series Miniature Industrial Relays and 97 Series Sockets			
060.48	Etiket plakası, 48 adet 6x12mm (CEMBRE termal taşıyıcılar), 097.00 etiket taşıyıcısına uygun	46 Series Miniature Industrial Relays and 97 Series Sockets			
	Not*: 99.02 modüller ve 86.30 timer kodları için bkz. sayfa XX	46 Series Miniature Industrial Relays and 97 Series Sockets			
	Not: Farklı gerilim versiyonları için bizimle iletişime geçiniz.	46 Series Miniature Industrial Relays and 97 Series Sockets			
	Not: Raylı versiyonları için bizimle iletişime geçiniz.	46 Series Miniature Industrial Relays and 97 Series Sockets			
55 Serisi Röleler ve 94 Serisi Soketler					
55.32.9.024.0040	55.32 Tip röleler	55 Series Relays and 94 Series Sockets			

55.33.8.230.0010	230VAC, 3 kontak 10A, test buton	230VAC, 3 CO 10A, test button	16.44	10	A
55.33.8.230.0050	230VAC, 3 kontak 10A, test buton + LED	230VAC, 3 CO 10A, test button + LED	18.70	10	A
55.34 Tip röleler					
55.34.9.012.0040	12VDC, 4 kontak 7A, test buton + mekanik indikatör	12VDC, 4 CO 7A, test button + mechanical indicator	13.82	10	A
55.34.9.012.0094	12VDC, 4 kontak 7A, test buton + mekanik indikatör + LED + diyot	12VDC, 4 CO 7A, test button + mechanical indicator + LED + diode	14.19	10	A
55.34.9.024.0040	24VDC, 4 kontak 7A, test buton + mekanik indikatör	24VDC, 4 CO 7A, test button + mechanical indicator	13.82	10	A
55.34.9.024.0094	24VDC, 4 kontak 7A, test buton + mekanik indikatör + LED + diyot	24VDC, 4 CO 7A, test button + mechanical indicator + LED + diode	14.19	10	A
55.34.9.110.0040	110VDC, 4 kontak 7A, test buton + mekanik indikatör	110VDC, 4 CO 7A, test button + mechanical indicator	15.25	10	A
55.34.9.110.0094	110VDC, 4 kontak 7A, test buton + mekanik indikatör + LED + diyot	110VDC, 4 CO 7A, test button + mechanical indicator + LED + diode	15.62	10	A
55.34.9.230.0040	230VAC, 4 kontak 7A, test buton + mekanik indikatör	230VAC, 4 CO 7A, test button + mechanical indicator	14.89	10	A
55.34.9.230.0094	230VAC, 4 kontak 7A, test buton + mekanik indikatör + LED	230VAC, 4 CO 7A, test button + mechanical indicator + LED	15.25	10	A
55.34 Tip röleler için soketler					
94.025MA	Vidalı soket, 3 kati, 094.91.3 plastik tutma/ayrma klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Sockets for 55.34 Type relays Screw terminal socket supplied with 094.91.3 plastic retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	7.66	10	A
94.025PA	Vidalı soket, 3 kati, 094.91.3 plastik tutma/ayrma klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Screw terminal socket supplied with 094.91.3 plastic retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	7.99	10	A
94.725MA	Vidalı soket, 2 kati, 094.71 metal klipsi dahli (23mm derinliğinde düşük profil soket), 99.01 modüllerle uyumlu	Screw terminal socket supplied with 094.71 metal retaining clip, 2 level, 23mm depth low profile, compatible with 99.01 modules	7.77	10	A
55.33 Tip röleler için soketler					
94.033MA	Vidalı soket, 3 kati, 094.71 metal klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Sockets for 55.33 Type relays Screw terminal socket supplied with 094.71 metal retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	8.77	10	A
94.033PA	Vidalı soket, 3 kati, 094.91.3 plastik tutma/ayrma klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Screw terminal socket supplied with 094.91.3 plastic retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	9.14	10	A
94.P35MA	Push-in soket, 3 kati, 094.71 metal klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Push-in terminal socket supplied with 094.71 metal retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	14.89	10	A
94.P35PA	Push-in soket, 3 kati, 094.91.3 plastik tutma/ayrma klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Push-in terminal socket supplied with 094.91.3 plastic retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	14.89	10	A
94.735MA	Vidalı soket, 2 kati, 094.71 metal klipsi dahli (23mm derinliğinde düşük profil soket), 99.01 modüllerle uyumlu	Screw terminal socket supplied with 094.71 metal retaining clip, 2 level, 23mm depth low profile, compatible with 99.01 modules	8.98	10	A
55.34 Tip röleler için soketler					
94.045MA	Vidalı soket, 3 kati, 094.71 metal klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Sockets for 55.34 Type relays Screw terminal socket supplied with 094.71 metal retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	8.77	10	A
94.045PA	Vidalı soket, 3 kati, 094.91.3 plastik tutma/ayrma klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Screw terminal socket supplied with 094.91.3 plastic retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	9.14	10	A
94.84.25MA	Vidalı soket, 2 kati, 094.71 metal klipsi dahli, 99.02* modüllerle uyumlu	Screw terminal socket supplied with 094.71 metal retaining clip, 2 level, compatible with 99.02 modules	8.53	10	A
94.84.25PA	Vidalı soket, 2 kati, 094.91.3 plastik tutma/ayrma klipsi dahli, 99.02* modüllerle uyumlu	Screw terminal socket supplied with 094.91.3 plastic retaining clip, 2 level, compatible with 99.02 modules	8.87	10	A
94.P45MA	Push-in soket, 3 kati, 094.71 metal klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Push-in terminal socket supplied with 094.71 metal retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	14.89	10	A
94.P45PA	Push-in soket, 3 kati, 094.91.3 plastik tutma/ayrma klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Push-in terminal socket supplied with 094.91.3 plastic retaining clip, 3 level, compatible with 99.02 modules and 86.30 timers	14.89	10	A
94.745MA	Vidalı soket, 2 kati, 094.71 metal klipsi dahli (23mm derinliğinde düşük profil soket), 99.01 modüllerle uyumlu	Screw terminal socket supplied with 094.71 metal retaining clip, 2 level, 23mm depth low profile, compatible with 99.01 modules	8.98	10	A
Aksesuarlar					
094.06	6 yollu jumper, 94.02, 94.03, 94.04, 94.84, 2 soketler için, mav	6-way jumper link for 94.02, 94.03, 94.04, 94.84, 2 sockets, blue	3.79	10	C
094.06.0	6 yollu jumper, 94.02, 94.03, 94.04, 94.84, 2 soketler için, siyah	6-way jumper link for 94.02, 94.03, 94.04, 94.84, 2 sockets, black	3.79	10	C
094.56	6 yollu jumper, 94.P3, 94.P4 soketler için, mav	6-way jumper link for 94.P3, 94.P4 sockets, blue	4.39	10	C
094.56.1	2 yollu jumper, 94.P3, 94.P4 soketler için, mav, 27.5mm	2-way jumper link for 94.P3, 94.P4 sockets, blue, 27.5mm	3.24	10	C
097.52	2 yollu jumper, 94.P3, 94.P4 soketler için, mav, 15.4mm	2-way jumper link for 94.P3, 94.P4 sockets, blue, 15.4mm	2.66	10	C
097.00	Etiket taşıyıcı, 060.48 etiketler için	Marker tag holder for tags 060.48 type	0.17	10	C
060.48	Etiket plakası, 48 adet (x12mm (CEMBRE Termal yazıcılar)), plastik tutma/ayrma klipsilerine veya etiket taşıyıcısına uygun	Sheet of marker tags for plastic retaining and release clip and for marker tag holder, 48 tags, 6 x 12 mm (CEMBRE thermal transfer printers)	12.37	1	C

Not: 99.02 modüller ve 86.30 timer kodları için bkz. sayfa XX
Not: Farklı gerilim versiyonları için bizi ile iletişime geçiniz.
Not: Raylı ulaşım versiyonları için bizi ile iletişime geçiniz.

Not: Please contact us for different voltage versions.
Not: Please contact us for railway versions.

56 Serisi Miniyatür Güç Röleleri ve 96 Serisi Soketler					
56.32 Tip röleler					
56.32.9.024.0040	24VDC, 2 kontak 12A, test buton + mekanik indikatör	24VDC, 2 CO 12A, test button + mechanical indicator	17.43	10	A
56.32.9.048.0040	48VDC, 2 kontak 12A, test buton + mekanik indikatör	48VDC, 2 CO 12A, test button + mechanical indicator	19.94	10	A
56.32.9.110.0040	110VDC, 2 kontak 12A, test buton + mekanik indikatör	110VDC, 2 CO 12A, test button + mechanical indicator	19.94	10	A
56.32.9.125.0040	125VDC, 2 kontak 12A, test buton + mekanik indikatör	125VDC, 2 CO 12A, test button + mechanical indicator	22.79	10	A
56.32.9.220.0040	220VDC, 2 kontak 12A, test buton + mekanik indikatör	220VDC, 2 CO 12A, test button + mechanical indicator	32.53	10	A
56.32.8.024.0040	12VAC, 2 kontak 12A, test buton + mekanik indikatör	12VAC, 2 CO 12A, test button + mechanical indicator	17.43	10	A
56.32.8.024.0094	24VAC, 2 kontak 12A, test buton + mekanik indikatör	24VAC, 2 CO 12A, test button + mechanical indicator	17.43	10	A
56.32.8.060.0040	60VAC, 2 kontak 12A, test buton + mekanik indikatör	60VAC, 2 CO 12A, test button + mechanical indicator	19.94	10	A
56.32.8.110.0040	110VAC, 2 kontak 12A, test buton + mekanik indikatör	110VAC, 2 CO 12A, test button + mechanical indicator	19.94	10	A
56.32.8.230.0040	230VAC, 2 kontak 12A, test buton + mekanik indikatör	230VAC, 2 CO 12A, test button + mechanical indicator	19.94	10	A
56.34 Tip röleler					
56.34.9.012.0040	12VDC, 4 kontak 12A, test buton + mekanik indikatör	12VDC, 4 CO 12A, test button + mechanical indicator	29.14	10	A
56.34.9.024.0040	24VDC, 4 kontak 12A, test buton + mekanik indikatör	24VDC, 4 CO 12A, test button + mechanical indicator	29.14	10	A
56.34.9.048.0040	48VDC, 4 kontak 12A, test buton + mekanik indikatör	48VDC, 4 CO 12A, test button + mechanical indicator	31.05	10	A
56.34.9.110.0040	110VDC, 4 kontak 12A, test buton + mekanik indikatör	110VDC, 4 CO 12A, test button + mechanical indicator	31.05	10	A
56.34.9.125.0040	125VDC, 4 kontak 12A, test buton + mekanik indikatör	125VDC, 4 CO 12A, test button + mechanical indicator	34.5	10	A
56.34.9.220.0040	220VDC, 4 kontak 12A, test buton + mekanik indikatör	220VDC, 4 CO 12A, test button + mechanical indicator	42.24	10	A
56.34.8.024.0040	24VAC, 4 kontak 12A, test buton + mekanik indikatör	24VAC, 4 CO 12A, test button + mechanical indicator	29.14	10	A
56.34.8.048.0040	48VAC, 4 kontak 12A, test buton + mekanik indikatör	48VAC, 4 CO 12A, test button + mechanical indicator	31.05	10	A
56.34.8.060.0040	60VAC, 4 kontak 12A, test buton + mekanik indikatör	60VAC, 4 CO 12A, test button + mechanical indicator	31.05	10	A
56.34.8.110.0040	110VAC, 4 kontak 12A, test buton + mekanik indikatör	110VAC, 4 CO 12A, test button + mechanical indicator	31.05	10	A
56.34.8.230.0040	230VAC, 4 kontak 12A, test buton + mekanik indikatör	230VAC, 4 CO 12A, test button + mechanical indicator	31.05	10	A
56.34.8.400.0040	400VAC, 4 kontak 12A, test buton + mekanik indikatör	400VAC, 4 CO 12A, test button + mechanical indicator	38.15	10	A
Soketler for 56.32 Type relays					
96.025MA	Vidalı soket, 094.71 metal klipsi dahli, 99.02* modüllerle uyumlu, 86.30* timer takabılır	Screw terminal socket supplied with 094.71 metal retaining clip, compatible with 99.02 modules and 86.30 timers	8.82	10	A
96.725MA	Vidalı soket, 094.71 metal klipsi dahli, 99.01* modüllerle uyumlu	Screw terminal socket supplied with 094.71 metal retaining clip, compatible with 99.01 modules	9.51	10	A
Soketler for 56.34 Type relays					
96.045MA	Vidalı soket, 096.71 metal klipsi dahli, 99.02* modüllerle uyumlu, 86.00 ve 86.30* timer takabılır	Screw terminal socket supplied with 096.71 metal retaining clip, compatible with 99.02 modules and 86.00 and 86.30 timers	10.94	10	A
96.745MA	Vidalı soket, 096.71 metal klipsi dahli, 99.01* modüllerle uyumlu	Screw terminal socket supplied with 096.71 metal retaining clip, compatible with 99.01 modules	11.79	10	A
Aksesuarlar					
Not: Please contact us for different voltage versions. Not: Please contact us for railway versions.					

60 Serisi (Okta) Röleleri ve 90 Serisi Soketler					
60.12 Tip röleler					
60.12.9.012.0040	12VDC, 2 kontak 10A, test buton + mekanik indikatör	12VDC, 2 CO 10A, test button + mechanical indicator	19.31	10	A
60.12.9.024.0040	24VDC, 2 kontak 10A, test buton + mekanik indikatör	24VDC, 2 CO 10A, test button + mechanical indicator	19.31	10	A
60.12.8.024.0040	24VAC, 2 kontak 10A, test buton + mekanik indikatör	24VAC, 2 CO 10A, test button + mechanical indicator	19.31	10	A
60.12.9.110.0040	110VDC, 2 kontak 10A, test buton + mekanik indikatör	110VDC, 2 CO 10A, test button + mechanical indicator	20.67	10	A
60.12.8.110.0040	110VAC, 2 kontak 10A, test buton + mekanik indikatör	110VAC, 2 CO 10A, test button + mechanical indicator	20.67	10	A
60.12.8.230.0040	230VAC, 2 kontak 10A, test buton + mekanik indikatör	230VAC, 2 CO 10A, test button + mechanical indicator	20.67	10	A
60.13 Tip röleler					
60.13.9.012.0040	12VDC, 3 kontak 10A, test buton + mekanik indikatör	12VDC, 3 CO 10A, test button + mechanical indicator	25.15	10	A
60.13.9.012.0074	12VDC, 3 kontak 10A, test buton + mekanik indikatör + LED + diyot	12VDC, 3 CO 10A, test button + mechanical indicator + LED + diode	25.15	10	A
60.13.9.024.0040	24VDC, 3 kontak 10A, test buton + mekanik indikatör	24VDC, 3 CO 10A, test button + mechanical indicator	25.15	10	A
60.13.9.024.0074	24VDC, 3 kontak 10A, test buton + mekanik indikatör + LED + diyot	24VDC, 3 CO 10A, test button + mechanical indicator + LED + diode	25.31	10	A
60.13.8.024.0040	24VAC, 3 kontak 10A, test buton + mekanik indikatör	24VAC, 3 CO 10A, test button + mechanical indicator	25.15	10	A
60.13.8.024.0074	24VAC, 3 kontak 10A, test buton + mekanik indikatör + LED + diyot	24VAC, 3 CO 10A, test button + mechanical indicator + LED + diode	25.31	10	A
60.13.9.110.0040	110VDC, 3 kontak 10A, test buton + mekanik indikatör	110VDC, 3 CO 10A, test button + mechanical indicator	23.3	10	A
60.13.9.110.0074	110VDC, 3 kontak 10A, test buton + mekanik indikatör + LED + diyot	110VDC, 3 CO 10A, test button + mechanical indicator + LED + diode	26.66	10	A
60.13.8.110.0040	110VAC, 3 kontak 10A, test buton + mekanik indikatör	110VAC, 3 CO 10A, test button + mechanical indicator	21.83	10	A
60.13.8.110.0074	110VAC, 3 kontak 10A, test buton + mekanik indikatör + LED	110VAC, 3 CO 10A, test button + mechanical indicator + LED	21.9	10	A
60.13.8.230.0040	230VAC, 3 kontak 10A, test buton + mekanik indikatör	230VAC, 3 CO 10A, test button + mechanical indicator	27.19	10	A
60.13.8.230.0074	230VAC, 3 kontak 10A, test buton + mekanik indikatör + LED	230VAC, 3 CO 10A, test button + mechanical indicator + LED	26.66	10	A
60.12 Tip röleler için soketler					
90.025MA	Vidalı soket, 090.33 metal klipsi dahli, 99.02 modüllerle uyumlu, 86.00 ve 86.30 timer takabılır	Sockets for 60.12 Type relays Screw terminal socket supplied with 090.33 metal retaining clip, compatible with 99.02 modules and 86.00 and 86.30 timers	8.16	10	A
90.205MA	Vidalı soket, 090.33 metal klipsi dahli, 99.01 modüllerle uyumlu	Screw terminal socket supplied with 090.33 metal retaining clip, compatible with 99.01 modules	7.7	10	A
90.225MA	Vidalı soket, 090.33 metal klipsi dahli, modül takilamaz	Screw terminal socket supplied with 090.33 metal retaining clip, no module compatible	7.7	10	A
90.265MA	Vidalı soket, 090.33 metal klipsi dahli, modül takilamaz	Screw terminal socket supplied with 090.33 metal retaining clip, no module compatible	7.7	10	A
60.13 Tip röleler için soketler					
90.035MA	Vidalı soket, 090.33 metal klipsi dahli, 99.02 modüllerle uyumlu, 86.00 ve 86.30* timer takabılır	Sockets for 60.13 Type relays Screw terminal socket supplied with 090.33 metal retaining clip, compatible with 99.02 modules and 86.00 and 86.30 timers	9.05	10	A
90.215MA	Vidalı soket, 090.33 metal klipsi dahli, 99.01 modüllerle uyumlu	Screw terminal socket supplied with 090.33 metal retaining clip, compatible with 99.01 modules	8.61	10	A
90.235MA	Vidalı soket, 090.33 metal klipsi dahli, modül takilamaz	Screw terminal socket supplied with 090.33 metal retaining clip, no module compatible	8.61	10	A
90.275MA	Vidalı soket, 090.33 metal klipsi dahli, modül takilamaz	Screw terminal socket supplied with 090.33 metal retaining clip, no module compatible	8.61	10	A
Aksesuarlar					
090.06	6 yollu jumper, 90.02 ve 90.03 soketler için, mav	6-way jumper link for 90.02 ve 90.03 sockets, blue	4.98	10	C
Not: 99.02 modüller ve 86.30 timer kodları için bkz. sayfa XX Not: Farklı gerilim versiyonları için bizi ile iletişime geçiniz. Not: Please contact us for different voltage versions.					

62 Serisi Güç Röleleri (16A) ve 92 Serisi Soketler					
62.32 Tip röleler					
62.32.9.024.4000	24VDC, 2 kontak 16A, AgSnO2 kontaklı	24VDC, 2 CO 16A, AgSnO2 contacts	20.05	10	A
62.32.8.230.4000	230VAC, 2 kontak 16A, AgSnO2 kontaklı	230VAC, 2 CO 16A, AgSnO2 contacts	21.37	10	A
62.32.9.024.4300	24VDC, 2 NO kontak 16A, AgSnO2 kontaklı, (3-zmm kontak aralığı), kesme kapasitesi DC1: 24V-16A/110V-11A/220V-0.7A	24VDC, 2 NO 16A, AgSnO2 contacts, (3-zmm contact gap), Breaking capacity DC1: 24V-16A/110V-11A/220V-0.7A	19.46	10	A
62.32.8.230.4300	230VAC, 2 NO kontak 16A, AgSnO2 kontaklı, (3-zmm kontak aralığı), kesme kapasitesi DC1: 24V-16A/110V-11A/220V-0.7A	230VAC, 2 NO 16A, AgSnO2 contacts, (3-zmm contact gap), Breaking capacity DC1: 24V-16A/110V-11A/220V-0.7A	20.81	10	A
62.33 Tip röleler					
62.33.9.024.4000	24VDC, 3 kontak 16A, AgSnO2 kontaklı	24VDC, 3 CO 16A, AgSnO2 contacts	21.02	10	A
62.33.8.230.4000	230VAC, 3 kontak 16A, AgSnO2 kontaklı	230VAC, 3 CO 16A, AgSnO2 contacts	22.38	10	A
62.33.9.024.4300	24VDC, 3 NO kontak 16A, AgSnO2 kontaklı, (3-zmm kontak aralığı), kesme kapasitesi DC1: 24V-16A/110V-11A/220V-0.7A	24VDC, 3 NO 16A, AgSnO2 contacts, (3-zmm contact gap), Breaking capacity DC1: 24V-16A/110V-11A/220V-0.7A	20.38	10	A
62.33.8.230.4300	230VAC, 3 NO kontak 16A, AgSnO2 kontaklı, (3-zmm kontak aralığı), kesme kapasitesi DC1: 24V-16A/110V-11A/220V-0.7A	230VAC, 3 NO 16A, AgSnO2 contacts, (3-zmm contact gap), Breaking capacity DC1: 24V-16A/110V-11A/220V-0.7A	21.73	10	A
62.31...4800 Tip Magnetik blow röleler					
62.31.9.024.4800	24VDC, 1 NO kontak 16A, AgSnO2 kontaklı, (2.4-zmm kontak aralığı), kesme kapasitesi DC1: 24V-16A/125V-16A/220V-12A	24VDC, 1 NO 16A, AgSnO2 contact, (2.4-zmm contact gap), Breaking capacity DC1: 24V-16A/125V-16A/220V-12A	24.28	10	A
62.31.9.110.4800	110VDC, 1 NO kontak 16A, AgSnO2 kontaklı, (2.4-zmm kontak aralığı),				

66.82.8.230.0303	230VAC, 2 NO kontak 30A, ATEX uyumlu Not: Farklı gerilim versiyonları için bizimle iletişime geçiniz.	230VAC, 2 NO 30A, ATEX compliant Note: Please contact us for different voltage versions.	serunuz	10	A
67 Serisi Yüksek Güç Röleleri (50A)					
67.22.9.012.4300	12VDC, 2 NO kontak 50A, 3mm kontak aralığı, AgSnO2	12VDC, 2 NO 50A, 3mm contacts gap, AgSnO2	44,1	10	A
67.23.9.012.4500	12VDC, 3 NO kontak 50A, 3mm kontak aralığı, AgSnO2	12VDC, 3 NO 50A, 3mm contacts gap, AgSnO2	46,42	10	A
67.22.9.012.4500	12VDC, 2 NO kontak 50A, 5,2mm kontak aralığı, AgSnO2	12VDC, 2 NO 50A, 5,2mm contacts gap, AgSnO2	44,1	10	A
67.23.9.012.4500	12VDC, 3 NO kontak 50A, 5,2mm kontak aralığı, AgSnO2	12VDC, 3 NO 50A, 5,2mm contacts gap, AgSnO2	46,42	10	A
67.22.9.024.4300	24VDC, 2 NO kontak 50A, 3mm kontak aralığı, AgSnO2	24VDC, 2 NO 50A, 3mm contacts gap, AgSnO2	44,1	10	A
67.23.9.024.4300	24VDC, 3 NO kontak 50A, 3mm kontak aralığı, AgSnO2	24VDC, 3 NO 50A, 3mm contacts gap, AgSnO2	46,42	10	A
67.22.9.024.4500	24VDC, 2 NO kontak 50A, 5,2mm kontak aralığı, AgSnO2	24VDC, 2 NO 50A, 5,2mm contacts gap, AgSnO2	44,1	10	A
67.23.9.024.4500	24VDC, 3 NO kontak 50A, 5,2mm kontak aralığı, AgSnO2	24VDC, 3 NO 50A, 5,2mm contacts gap, AgSnO2	46,42	10	A
68 Serisi Yüksek Güç Röleleri (32 - 40 - 100A)					
68.22.9.012.4300	12VDC, 2 NO kontak 100A, 3,6mm kontak aralığı, AgSnO2	12VDC, 2 NO 100A, 3,6mm contacts gap, AgSnO2	45,73	10	A
68.23.9.012.4300	12VDC, 2 NO + 1 NC kontak 100A/3A, 3,6mm kontak aralığı, AgSnO2	12VDC, 2 NO + 1 NC 100A/3A, 3,6mm contacts gap, AgSnO2	48,81	10	A
68.24.9.012.4300	12VDC, 4 NO kontak 40A, 3,6mm kontak aralığı, AgSnO2	12VDC, 4 NO 40A, 3,6mm contacts gap, AgSnO2	47,31	10	A
68.25.9.012.4300	12VDC, 4 NO + 1 NC kontak 40A/3A, 3,6mm kontak aralığı, AgSnO2	12VDC, 4 NO + 1 NC 40A/3A, 3,6mm contacts gap, AgSnO2	52,05	10	A
68.54.9.012.4300	12VDC, 4 NO kontak 32A, 3,6mm kontak aralığı, AgSnO2	12VDC, 4 NO 32A, 3,6mm contacts gap, AgSnO2	47,31	10	A
68.55.9.012.4300	12VDC, 4 NO + 1 NC kontak 32A/3A, 3,6mm kontak aralığı, AgSnO2	12VDC, 4 NO + 1 NC 32A/3A, 3,6mm contacts gap, AgSnO2	52,05	10	A
68.22.9.024.4300	24VDC, 2 NO kontak 100A, 3,6mm kontak aralığı, AgSnO2	24VDC, 2 NO 100A, 3,6mm contacts gap, AgSnO2	45,73	10	A
68.23.9.024.4300	24VDC, 2 NO + 1 NC kontak 100A/3A, 3,6mm kontak aralığı, AgSnO2	24VDC, 2 NO + 1 NC 100A/3A, 3,6mm contacts gap, AgSnO2	48,81	10	A
68.24.9.024.4300	24VDC, 4 NO kontak 40A, 3,6mm kontak aralığı, AgSnO2	24VDC, 4 NO 40A, 3,6mm contacts gap, AgSnO2	47,31	10	A
68.25.9.024.4300	24VDC, 4 NO + 1 NC kontak 40A/3A, 3,6mm kontak aralığı, AgSnO2	24VDC, 4 NO + 1 NC 40A/3A, 3,6mm contacts gap, AgSnO2	52,05	10	A
68.54.9.024.4300	24VDC, 4 NO kontak 32A, 3,6mm kontak aralığı, AgSnO2	24VDC, 4 NO 32A, 3,6mm contacts gap, AgSnO2	47,31	10	A
68.55.9.024.4300	24VDC, 4 NO + 1 NC kontak 32A/3A, 3,6mm kontak aralığı, AgSnO2	24VDC, 4 NO + 1 NC 32A/3A, 3,6mm contacts gap, AgSnO2	52,05	10	A
69 Serisi Yüksek Güç Röleleri (32 - 40 - 100A)					
69.22.9.012.4300	12VDC, 2 NO kontak 100A, 3,6mm kontak aralığı, AgSnO2	12VDC, 2 NO 100A, 3,6mm contacts gap, AgSnO2	45,73	10	A
69.23.9.012.4300	12VDC, 2 NO + 1 NC kontak 100A/3A, 3,6mm kontak aralığı, AgSnO2	12VDC, 2 NO + 1 NC 100A/3A, 3,6mm contacts gap, AgSnO2	48,81	10	A
69.24.9.012.4300	12VDC, 4 NO kontak 40A, 3,6mm kontak aralığı, AgSnO2	12VDC, 4 NO 40A, 3,6mm contacts gap, AgSnO2	47,31	10	A
69.25.9.012.4300	12VDC, 4 NO + 1 NC kontak 40A/3A, 3,6mm kontak aralığı, AgSnO2	12VDC, 4 NO + 1 NC 40A/3A, 3,6mm contacts gap, AgSnO2	52,05	10	A
69.54.9.012.4300	12VDC, 4 NO kontak 32A, 3,6mm kontak aralığı, AgSnO2	12VDC, 4 NO 32A, 3,6mm contacts gap, AgSnO2	47,31	10	A
69.55.9.012.4300	12VDC, 4 NO + 1 NC kontak 32A/3A, 3,6mm kontak aralığı, AgSnO2	12VDC, 4 NO + 1 NC 32A/3A, 3,6mm contacts gap, AgSnO2	52,05	10	A
70 Serisi Fırcılı Güç Kontaktı Emniyet Röleleri					
50.12.9.024.1000	EN 61810-3 (önceki EN 50205) e göre, Tip B 24VDC, 2 kutup (2CO) BA, PCB	According to EN 61810-3 (previously EN 50205), Type B 24VDC, 2 pole (2CO) BA, PCB	14,87	50	A
48.12.9.024.50075MA	24VDC, 2 kutup (2CO) BA + metal kipsli vidalı soket (bakım halinde)	24VDC, 2 pole (2CO) BA + screw terminal socket supplied metal retaining clip (complete code)	26,31	10	A
50.14.9.024.4230	EN 61810 (önceki EN 50205) e göre, Tip A 24VDC, 4 kutup (2NO+2NC) BA, PCB	According to EN 61810 (previously EN 50205), Type A 24VDC, 4 pole (2NO+2NC) BA, PCB	serunuz	10	A
50.14.9.024.4310	24VDC, 4 kutup (1NO+3NC) BA, PCB	24VDC, 4 pole (1NO+3NC) BA, PCB	serunuz	10	A
50.16.9.024.5420	24VDC, 6 kutup (4NO+2NC) BA, PCB	24VDC, 6 pole (4NO+2NC) BA, PCB	serunuz	10	A
50.16.9.024.5330	24VDC, 6 kutup (1NO+3NC) BA, PCB	24VDC, 6 pole (1NO+3NC) BA, PCB	serunuz	10	A
50.16.9.024.5510	24VDC, 6 kutup (1NO+3NC) BA, PCB	24VDC, 6 pole (1NO+3NC) BA, PCB	serunuz	10	A
75 Serisi Fırcılı Güç Kontaktı Emniyet Röleleri					
EN 61810-3 (önceki EN 50205) e göre, Tip A EN 61508 e göre SIL 2, EN 62061 e göre SIL 2 ye kadar ve IEC 13849-1 e göre PL 3 ye kadar	EN 61810-3 (previously EN 50205), Type A According to EN 61508, for use in functional safety application according to IEC 13849-1 up to PL 3	58,35	5	A	
75.32.9.024.5110	24VDC, 2 kutup (1NO+1NC) 6A	24VDC, 2 pole (1NO+1NC) 6A	58,35	5	A
75.32.9.024.5120	24VDC, 3 kutup (1NO+1NC) 10A	24VDC, 3 pole (1NO+1NC) 10A	55,11	5	A
75.34.9.024.4230	24VDC, 4 kutup (2NO+2NC) 6A	24VDC, 4 pole (2NO+2NC) 6A	94,8	5	A
75.34.9.024.4310	24VDC, 4 kutup (1NO+1NC) 6A	24VDC, 4 pole (1NO+1NC) 6A	94,8	5	A
75.36.9.024.5420	24VDC, 6 kutup (4NO+2NC) 6A	24VDC, 6 pole (4NO+2NC) 6A	116,67	5	A
75.36.9.024.5510	24VDC, 6 kutup (1NO+3NC) 6A	24VDC, 6 pole (1NO+3NC) 6A	130,25	5	A
EN 61810-3 (önceki EN 50205) e göre, Tip A, SIL 3 e kadar EN 61508 e göre SIL 3, EN 62061 e göre SIL 3 e kadar ve IEC 13849-1 e göre PL 3 ye kadar	EN 61810-3 (previously EN 50205), Type A, up to SIL 3 SIL3 evaluated according to EN 61508, for use in functional safety application according to IEC 13849-1 up to PL 3	114,06	5	A	
75.3.9.024.0211	Çift kanal mimarisi (1oo2) 2 NO kontak, 1 geribildirim kontak ve 1 yardımcı kontak ile 24VDC, 3 kutup (1NO+1NC) 6A, 1 yardımcı kontak Not: Farklı gerilim versiyonları için bizimle iletişime geçiniz. Not: Raylı ulaşım versiyonları için bizimle iletişime geçiniz.	Double channel architecture (1oo2) with 2 NO contact, 1 feedback contact and 1 auxiliary contact 24VDC, 3 pole (1NO+1NC) 6A, 1 auxiliary contact Note: Please contact us for different voltage versions. Note: Please contact us for railway versions.	114,06	5	A
13 Serisi Sessiz Elektronik Step Röleleri (Darbe Akım Anahatları)					
13.81.8.230.0000	Elektronik step röle, 230VAC, 1 NO 16A	Electronic step relay, 230VAC, 1 NO 16A	53,11	5	D
13.01.8.230.0000	Elektronik step/monostabile röle, 24VAC/DC, 1 CO 16A	Electronic step/monostable relay, 24VAC/DC, 1 CO 16A	48,17	5	D
13.01.8.230.0000	Elektronik step/monostabile röle, 230VAC, 1 CO 16A	Electronic step/monostable relay, 230VAC, 1 CO 16A	53,11	5	D
13.61.0.024.0000	Çok fonksiyonlu elektronik step/zamanlı step/monostabile röle, 12...24VAC/DC, 1 CO 16A	Multifunction electronic step/monostable relay, 12...24VAC/DC, 1 CO 16A	39,34	5	D
13.61.8.230.0000	Çok fonksiyonlu elektronik step/zamanlı step/monostabile röle, 110...240VAC, 1 NO 16A	Multifunction electronic step/monostable relay, 110...240VAC, 1 NO 16A	48,17	5	D
20 Serisi Step Röleleri (Darbe Akım Anahatları)					
20.21.9.024.2000	Step röle, 12VDC, tek kutup, 1 NO	Step relay, 12VDC, single phase, 1 NO	29,21	5	C
20.21.9.024.0000	Step röle, 24VDC, tek kutup, 1 NO	Step relay, 24VDC, single phase, 1 NO	29,21	5	C
20.22.9.024.0000	Step röle, 24VDC, çift kutup, 2 NO	Step relay, 24VDC, double phase, 2 NO	34,88	5	C
20.23.9.024.0000	Step röle, 24VDC, çift kutup, 1 NO + 1 NC	Step relay, 24VDC, double phase, 1 NO + 1 NC	34,88	5	C
20.24.9.024.0000	Step röle, 24VDC, çift kutup, 2 NO, 4 sekans	Step relay, 24VDC, double phase, 2 NO, 4 sequence	34,88	5	C
20.21.8.230.0000	Step röle, 230VAC, tek kutup, 1 NO	Step relay, 230VAC, single phase, 1 NO	34,88	5	C
20.22.8.230.0000	Step röle, 230VAC, çift kutup, 2 NO	Step relay, 230VAC, double phase, 2 NO	34,88	5	C
20.23.8.230.0000	Step röle, 230VAC, çift kutup, 1 NO + 1 NC	Step relay, 230VAC, double phase, 1 NO + 1 NC	34,88	5	C
20.24.8.230.0000	Step röle, 230VAC, çift kutup, 2 NO, 4 sekans	Step relay, 230VAC, double phase, 2 NO, 4 sequence	34,88	5	C
60.13.4. Tip Akım Algılama Röleleri					
60.13.4.012.0040	DC Akım algılama, 3 kontak 100 mA DC	DC Current sensing, 3 contacts 100 mA DC	44,19	10	A
60.13.4.022.0040	200 mA DC	200 mA DC	44,19	10	A
60.13.4.032.0040	300 mA DC	300 mA DC	44,19	10	A
60.13.4.042.0040	400 mA DC	400 mA DC	44,19	10	A
60.13.4.052.0040	500 mA DC	500 mA DC	44,19	10	A
60.13.4.102.0040	1 A DC	1 A DC	44,19	10	A
60.13.4.122.0040	1,2 A DC	1,2 A DC	44,19	10	A
60.13.4.162.0040	1,6 A DC	1,6 A DC	44,19	10	A
60.13.4.202.0040	2 A DC	2 A DC	44,19	10	A
60.13.4.252.0040	2,5 A DC	2,5 A DC	44,19	10	A
60.13.4.402.0040	4 A DC	4 A DC	44,19	10	A
60.13.4.502.0040	5 A DC	5 A DC	44,19	10	A
60.13.4.011.0040	AC Akım algılama, 3 kontak 100 mA AC	AC Current sensing, 3 contacts 100 mA AC	44,19	10	A
60.13.4.021.0040	200 mA AC	200 mA AC	44,19	10	A
60.13.4.031.0040	300 mA AC	300 mA AC	44,19	10	A
60.13.4.041.0040	400 mA AC	400 mA AC	44,19	10	A
60.13.4.051.0040	500 mA AC	500 mA AC	44,19	10	A
60.13.4.101.0040	1 A AC	1 A AC	44,19	10	A
60.13.4.121.0040	1,2 A AC	1,2 A AC	44,19	10	A
60.13.4.161.0040	1,6 A AC	1,6 A AC	44,19	10	A
60.13.4.201.0040	2 A AC	2 A AC	44,19	10	A
60.13.4.251.0040	2,5 A AC	2,5 A AC	44,19	10	A
60.13.4.401.0040	4 A AC	4 A AC	44,19	10	A
60.13.4.501.0040	5 A AC	5 A AC	44,19	10	A
77 Serisi Hockey Disk Tipi SSR					
77.1.9.024.8250	1-Faz modeller Giriş 24VDC, çıkış 25A 240VAC (24...280VAC)	1-Phase models Input 24VDC, output 25A 240VAC (24...280VAC)	35,28	10	C
77.1.9.024.8250	Giriş 24VDC, çıkış 40A 240VAC (24...280VAC)	Input 24VDC, output 40A 240VAC (24...280VAC)	48,25	10	C
77.1.9.024.8250	Giriş 24VDC, çıkış 60A 240VAC (24...280VAC)	Input 24VDC, output 60A 240VAC (24...280VAC)	37,54	10	C
77.1.9.024.8250	Giriş 24VDC, çıkış 100A 240VAC (24...280VAC)	Input 24VDC, output 100A 240VAC (24...280VAC)	56,03	10	C
77.1.9.024.8250	Giriş 24VDC, çıkış 125A 240VAC (24...280VAC)	Input 24VDC, output 125A 240VAC (24...280VAC)	70,26	10	C
77.1.9.024.8650	Giriş 24VDC, çıkış 25A 600VAC (24...660VAC)	Input 24VDC, output 25A 600VAC (24...660VAC)	41,52	10	C
77.1.9.024.8650	Giriş 24VDC, çıkış 40A 600VAC (24...660VAC)	Input 24VDC, output 40A 600VAC (24...660VAC)	42,95	10	C
77.1.9.024.8650	Giriş 24VDC, çıkış 60A 600VAC (24...660VAC)	Input 24VDC, output 60A 600VAC (24...660VAC)	53,12	10	C
77.1.9.024.8650	Giriş 24VDC, çıkış 80A 600VAC (24...660VAC)	Input 24VDC, output 80A 600VAC (24...660VAC)	59,48	10	C
77.1.9.024.8650	Giriş 24VDC, çıkış 100A 600VAC (24...660VAC)	Input 24VDC, output 100A 600VAC (24...660VAC)	78,88	10	C
77.1.9.024.8650	Giriş 24VDC, çıkış 125A 600VAC (24...660VAC)	Input 24VDC, output 125A 600VAC (24...660VAC)	98,92	10	C
77.1.9.024.8671	3-Faz modeller Giriş 24VDC, çıkış 25A 600VAC (24...660VAC), 3-faz	3-Phase models Input 24VDC, output 25A 600VAC (24...660VAC), 3-phase	123,72	10	C
77.1.9.024.8671	Giriş 24VDC, çıkış 40A 600VAC (24...660VAC), 3-faz	Input 24VDC, output 40A 600VAC (24...660VAC), 3-phase	145,68	10	C
77.1.9.024.8671	Giriş 24VDC, çıkış 60A 600VAC (24...660VAC), 3-faz	Input 24VDC, output 60A 600VAC (24...660VAC), 3-phase	204,45	10	C
77.1.9.024.8671	Giriş 24VDC, çıkış 80A 600VAC (24...660VAC), 3-faz	Input 24VDC, output 80A 600VAC (24...660VAC), 3-phase	276,18	10	C
8A Serisi Programlanabilir Logic Röleleri					
8A.04.9.024.8300	Ana modüller - ARDUINO IDE veya IEC 61131-3 dilleri (LD - SFC - FBD - ST - IL) ile programlanabilir	Base modules - Programming with ARDUINO IDE or IEC 61131-3 dilleri (LD - SFC - FBD - ST - IL)	167,63	1	D
8A.04.9.024.8310	OPTA LITE, 8IN (Di veya Ai (0...10V)), 4OUT (Röle, NO), USB (Type-C), Modbus TCP/IP	OPTA LITE, 8IN (Di or Ai (0...10V)), 4OUT (Relay, NO), USB (Type-C), Modbus TCP/IP	183,86	1	D
8A.04.9.024.8320	OPTA ADVANCED, 8IN (Di veya Ai (0...10V)), 4OUT (Röle, NO), USB (Type-C), Modbus TCP/IP + Modbus RS485	OPTA ADVANCED, 8IN (Di or Ai (0...10V)), 4OUT (Relay, NO), USB (Type-C), Modbus TCP/IP + Modbus RS485	220,63	1	D
8A.04.9.024.8330	OPTA ADVANCED, 8IN (Di veya Ai (0...10V)), 4OUT (Röle, NO), USB (Type-C), Modbus TCP/IP + Modbus RS485 + WiFi/BLE	OPTA ADVANCED, 8IN (Di or Ai (0...10V)), 4OUT (Relay, NO), USB (Type-C), Modbus TCP/IP + Modbus RS485 + WiFi/BLE	220,63	1	D
8A.38.9.024.1000	Genişleme modülleri	Expansion modules	156,82	1	D
8A.38.9.024.1000	Dijital genişleme modülü, 16IN (Di veya Ai (0...10V)), 8OUT (Röle, NO)	Digital expansion module, 16IN (Di or Ai (0...10V)), 8OUT (Relay, NO)	167,63	1	D
8A.38.9.024.1000	Dijital genişleme modülü, 16IN (Di veya Ai (0...10V)), 8OUT (SSR, 2A)	Digital expansion module, 16IN (Di or Ai (0...10V)), 8OUT (SSR, 2A)	167,63	1	D
8A.38.9.024.1000	Analog genişleme modülü, 6AI (0...10V, 4...20 mA), PT100, 2AO (0...10V, 4...20 mA), 4 PWM out 10kHz	Analog expansion module, 6AI (0...10V, 4...20 mA), PT100, 2AO (0...10V, 4...20 mA), 4 PWM out 10kHz	254,15	1	D
8A.38.9.024.1000	Not: 5 adet genişleme modülü bağlanabilir (karşık)	Note: 5 expansion modules can be connected to 1 main module (mixed)			
78.12.1.230.2482	Güc Klavye OPTA için güç kaynağı, 24VDC 12W çıkış, siyah renk	Power Supply for OPTA, 24VDC 12W output, black color	76,79	1	C
Sorunuz	OPTA Codesys	OPTA Codesys			D
EM Serisi Tek Faz					

80 Serisi Timer'lar		80 Series Timers			
Timerlar		Timers			
80.11.240.0000	On-delay timer, 24...240VAC/DC, 1CO, (0.1...2)sn, (0.1...2)dk, (0.1...20)dk, (0.1...2)saat, (1...24)saat	On-delay timer; 24...240VAC/DC, 1CO, (0.1...2)s, (0.1...2)m, (1...20)min, (0.1...2)h, (1...24)h	65.74	5	A
80.01.240.0000	Çok-fonksiyonlu, 12...240VAC/DC, 1CO, (0.1...2)sn, (0.1...2)dk, (0.1...20)dk, (0.1...2)saat, (1...24)saat	Multi-function, 12...240VAC/DC, 1CO, (0.1...2)s, (0.1...2)m, (1...20)min, (0.1...2)h, (1...24)h	89.96	5	A
80.51.240.0000	Yeni Çok-fonksiyonlu, 24...240VAC/DC, 1CO, (0.1...2)sn, (0.1...2)dk, (0.1...20)dk, (0.1...2)saat, (1...24)saat	NEW! Multi-function, 24...240VAC/DC, 1CO, (0.1...2)s, (0.1...2)m, (1...20)min, (0.1...2)h, (1...24)h	59.61	5	A
84.02.0.30.0000	SMARTimer, multifunction digital timer, 110...240VAC/DC, 2 bağımsız kanal, NFC ile programlama	SMARTimer, multifunction digital timer, 110...240VAC/DC, 2 independent channels, 16A, with NFC programming	133.19	5	A
80.82.0.240.0000	Multi-voltage; 17.5mm wide; 2NO 6A; Star-Delta (SD), 24...240VAC/DC Not: Raylı uluşum versiyonları için bizimle iletişime geçiniz.	Star-Delta relay Multi-voltage; 17.5mm wide; 2NO 6A; Star-Delta (SD), 24...240VAC/DC Note: Please contact us for railway versions	91.35	5	A
22 Serisi Sessiz Kontaktörler		22 Series Silent Contactors			
25 A Kontaktörler		25 A Contactors			
22.32.0.024.4320	24VAC/DC bobin, 25 A (AC3 10A), 2 NO, Mekanik indikatör + Led, AgSnO2	24VAC/DC coil, 25 A (AC3 10A), 2 NO, Mechanical indicator + Led, AgSnO2	37.95	5	C
22.32.0.024.4340	24VAC/DC bobin, 25 A (AC3 10A), 2 NO, Auto-On-Off seçici + Mekanik indikatör + Led, AgSnO2	24VAC/DC coil, 25 A (AC3 10A), 2 NO, Auto-On-Off selector + Mechanical indicator + Led, AgSnO2	42.69	5	C
22.34.0.024.4320	24VAC/DC bobin, 25 A (AC3 10A), 4 NO, Mekanik indikatör + Led, AgSnO2	24VAC/DC coil, 25 A (AC3 10A), 4 NO, Mechanical indicator + Led, AgSnO2	53.73	5	C
22.34.0.024.4340	24VAC/DC bobin, 25 A (AC3 10A), 4 NO, Auto-On-Off seçici + Mekanik indikatör + Led, AgSnO2	24VAC/DC coil, 25 A (AC3 10A), 4 NO, Auto-On-Off selector + Mechanical indicator + Led, AgSnO2	58.51	5	C
22.32.0.120.4320	120VAC/DC bobin, 25 A (AC3 10A), 2 NO, Mekanik indikatör + Led, AgSnO2	120VAC/DC coil, 25 A (AC3 10A), 2 NO, Mechanical indicator + Led, AgSnO2	37.95	5	C
22.32.0.120.4340	120VAC/DC bobin, 25 A (AC3 10A), 2 NO, Auto-On-Off seçici + Mekanik indikatör + Led, AgSnO2	120VAC/DC coil, 25 A (AC3 10A), 2 NO, Auto-On-Off selector + Mechanical indicator + Led, AgSnO2	42.69	5	C
22.34.0.120.4320	120VAC/DC bobin, 25 A (AC3 10A), 4 NO, Mekanik indikatör + Led, AgSnO2	120VAC/DC coil, 25 A (AC3 10A), 4 NO, Mechanical indicator + Led, AgSnO2	53.73	5	C
22.34.0.120.4340	120VAC/DC bobin, 25 A (AC3 10A), 4 NO, Auto-On-Off seçici + Mekanik indikatör + Led, AgSnO2	120VAC/DC coil, 25 A (AC3 10A), 4 NO, Auto-On-Off selector + Mechanical indicator + Led, AgSnO2	58.51	5	C
22.32.0.230.4320	230VAC/DC bobin, 25 A (AC3 10A), 2 NO, Mekanik indikatör + Led, AgSnO2	230VAC/DC coil, 25 A (AC3 10A), 2 NO, Mechanical indicator + Led, AgSnO2	37.95	5	C
22.32.0.230.4340	230VAC/DC bobin, 25 A (AC3 10A), 2 NO, Auto-On-Off seçici + Mekanik indikatör + Led, AgSnO2	230VAC/DC coil, 25 A (AC3 10A), 2 NO, Auto-On-Off selector + Mechanical indicator + Led, AgSnO2	42.69	5	C
22.34.0.230.4320	230VAC/DC bobin, 25 A (AC3 10A), 4 NO, Mekanik indikatör + Led, AgSnO2	230VAC/DC coil, 25 A (AC3 10A), 4 NO, Mechanical indicator + Led, AgSnO2	53.73	5	C
22.34.0.230.4340	230VAC/DC bobin, 25 A (AC3 10A), 4 NO, Auto-On-Off seçici + Mekanik indikatör + Led, AgSnO2	230VAC/DC coil, 25 A (AC3 10A), 4 NO, Auto-On-Off selector + Mechanical indicator + Led, AgSnO2	58.51	5	C
22.72.0.024.1310	24VAC/DC bobin, 32 A (AC3 9A), 2 NO, Mekanik indikatör, AgNi	24VAC/DC coil, 32 A (AC3 9A), 2 NO, Mechanical indicator, AgNi	44.79	10	C
22.74.0.024.1310	24VAC/DC bobin, 32 A (AC3 8.5A), 4 NO, Mekanik indikatör, AgNi	24VAC/DC coil, 32 A (AC3 8.5A), 4 NO, Mechanical indicator, AgNi	63.47	5	C
22.72.0.230.1310	230VAC/DC bobin, 32 A (AC3 9A), 2 NO, Mekanik indikatör, AgNi	230VAC/DC coil, 32 A (AC3 9A), 2 NO, Mechanical indicator, AgNi	44.79	10	C
22.74.0.230.1310	230VAC/DC bobin, 32 A (AC3 8.5A), 2 NO + 2 NC, Mekanik indikatör, AgNi	230VAC/DC coil, 32 A (AC3 8.5A), 2 NO + 2 NC, Mechanical indicator, AgNi	63.47	5	C
22.74.0.230.1310	230VAC/DC bobin, 32 A (AC3 8.5A), 4 NO, Mekanik indikatör, AgNi	230VAC/DC coil, 32 A (AC3 8.5A), 4 NO, Mechanical indicator, AgNi	63.47	5	C
22.44.0.024.4610	24VAC/DC bobin, 40 A (AC3 22A), 2 NO + 2 NC, Mekanik indikatör, AgSnO2	24VAC/DC coil, 40 A (AC3 22A), 2 NO + 2 NC, Mechanical indicator, AgSnO2	95.84	5	C
22.44.0.024.4310	24VAC/DC bobin, 40 A (AC3 22A), 4 NO, Mekanik indikatör, AgSnO2	24VAC/DC coil, 40 A (AC3 22A), 4 NO, Mechanical indicator, AgSnO2	95.84	5	C
22.44.0.230.4610	230VAC/DC bobin, 40 A (AC3 22A), 2 NO + 2 NC, Mekanik indikatör, AgSnO2	230VAC/DC coil, 40 A (AC3 22A), 2 NO + 2 NC, Mechanical indicator, AgSnO2	95.84	5	C
22.44.0.230.4310	230VAC/DC bobin, 40 A (AC3 22A), 4 NO, Mekanik indikatör, AgSnO2	230VAC/DC coil, 40 A (AC3 22A), 4 NO, Mechanical indicator, AgSnO2	95.84	5	C
22.64.0.024.4610	24VAC/DC bobin, 63 A (AC3 30A), 2 NO + 2 NC, Mekanik indikatör, AgSnO2	24VAC/DC coil, 63 A (AC3 30A), 2 NO + 2 NC, Mechanical indicator, AgSnO2	105.41	5	C
22.64.0.024.4310	24VAC/DC bobin, 63 A (AC3 30A), 4 NO, Mekanik indikatör, AgSnO2	24VAC/DC coil, 63 A (AC3 30A), 4 NO, Mechanical indicator, AgSnO2	105.41	5	C
22.64.0.230.4610	230VAC/DC bobin, 63 A (AC3 30A), 2 NO + 2 NC, Mekanik indikatör, AgSnO2	230VAC/DC coil, 63 A (AC3 30A), 2 NO + 2 NC, Mechanical indicator, AgSnO2	105.41	5	C
22.64.0.230.4310	230VAC/DC bobin, 63 A (AC3 30A), 4 NO, Mekanik indikatör, AgSnO2	230VAC/DC coil, 63 A (AC3 30A), 4 NO, Mechanical indicator, AgSnO2	105.41	5	C
Not: Farklı gerilim versiyonları için bizimle iletişime geçiniz. Not: Raylı uluşum versiyonları için bizimle iletişime geçiniz.		Note: Please contact us for different voltage versions. Note: Please contact us for railway versions			
6K Serisi Endüstriyel Kontaktörler		6K Series Industrial Contactors			
Kontaktörler		Contactors			
6K.04.8.110.4809	110VAC bobin, 9 A-400V AC/3, 3 NO + 1 NO dahili yrd. kontak	110VAC coil, 9 A-400V AC/3, 3 NO + 1 NO auxiliary contact	32.64	5	C
6K.04.8.110.4812	110VAC bobin, 11 A-400V AC/3, 3 NO + 1 NO dahili yrd. kontak	110VAC coil, 11 A-400V AC/3, 3 NO + 1 NO auxiliary contact	41.23	5	C
6K.04.8.230.4309	230VAC bobin, 9 A-400V AC/3, 4 NO	230VAC coil, 9 A-400V AC/3, 4 NO	34.82	5	C
6K.04.8.230.4309	230VAC bobin, 9 A-400V AC/3, 3 NO + 1 NO dahili yrd. kontak	230VAC coil, 9 A-400V AC/3, 3 NO + 1 NO auxiliary contact	32.64	5	C
6K.04.8.230.4312	230VAC bobin, 12 A-400V AC/3, 4 NO	230VAC coil, 12 A-400V AC/3, 4 NO	43.74	5	C
6K.04.8.230.4812	230VAC bobin, 12 A-400V AC/3, 3 NO + 1 NO dahili yrd. kontak	230VAC coil, 12 A-400V AC/3, 3 NO + 1 NO auxiliary contact	41.23	5	C
6K.14.8.230.4818	230VAC bobin, 18 A-400V AC/3, 3 NO + 1 NO dahili yrd. kontak	230VAC coil, 18 A-400V AC/3, 3 NO + 1 NO auxiliary contact	53.88	5	C
6K.13.8.230.4324	230VAC bobin, 24 A-400V AC/3, 3 NO	230VAC coil, 24 A-400V AC/3, 3 NO	80.69	5	C
6K.13.8.230.4324	230VAC bobin, 32 A-400V AC/3, 3 NO	230VAC coil, 32 A-400V AC/3, 3 NO	106.73	5	C
6K.13.8.230.4350	230VAC bobin, 50 A-400V AC/3, 3 NO	230VAC coil, 50 A-400V AC/3, 3 NO	173.1	5	C
6K.13.8.230.4374	230VAC bobin, 74 A-400V AC/3, 3 NO	230VAC coil, 74 A-400V AC/3, 3 NO	281.03	5	C
Yardımcı kontaktlar		Auxiliary contacts			
6K.03	6K.04 kontaktörleri için yardımcı kontak, 1 NO + 1 NC, 2A-400V AC/5	1 NO + 1 NC Auxiliary contact for 6K.04 contactors, 2A-400V AC/5	12.31	5	C
6K.06	6K.04 kontaktörleri için yardımcı kontak, 2 NO + 2 NC, 2A-400V AC/5	2 NO + 2 NC Auxiliary contact for 6K.04 contactors, 2A-400V AC/5	21.47	5	C
6K.06	6K.13 ve 6K.14 kontaktörleri için yardımcı kontak, 1 NO, 2A-400V AC/5	1 NO Auxiliary contact for 6K.13 and 6K.14 contactors, 2A-400V AC/5	6.18	5	C
6K.06	6K.13 ve 6K.14 kontaktörleri için yardımcı kontak, 1 NC, 2A-400V AC/5	1 NC Auxiliary contact for 6K.13 and 6K.14 contactors, 2A-400V AC/5	6.18	5	C
Termik röleler		Thermal overload relays			
6K.70.0.000.1827	6K.04 için 1.8-2.7 A	For 6K.04, 1.8-2.7 A	67.64	Sorumuz	C
6K.70.0.000.1704	6K.04 için 2.7-4 A	For 6K.04, 2.7-4 A	67.64	Sorumuz	C
6K.70.0.000.0406	6K.04 için 4-6 A	For 6K.04, 4-6 A	67.64	Sorumuz	C
6K.70.0.000.0609	6K.04 için 6-8 A	For 6K.04, 6-8 A	76.91	Sorumuz	C
6K.70.0.000.0811	6K.04 için 8-11 A	For 6K.04, 8-11 A	76.91	Sorumuz	C
6K.71.0.000.1827	6K.14 ve 6K.13 için 1.8-2.7 A	For 6K.14 and 6K.13, 1.8-2.7 A	73.43	Sorumuz	C
6K.71.0.000.1704	6K.14 ve 6K.13 için 2.7-4 A	For 6K.14 and 6K.13, 2.7-4 A	73.43	Sorumuz	C
6K.71.0.000.0406	6K.14 ve 6K.13 için 4-6 A	For 6K.14 and 6K.13, 4-6 A	73.43	Sorumuz	C
6K.71.0.000.0609	6K.14 ve 6K.13 için 6-8 A	For 6K.14 and 6K.13, 6-8 A	85.56	Sorumuz	C
6K.71.0.000.0811	6K.14 ve 6K.13 için 8-11 A	For 6K.14 and 6K.13, 8-11 A	85.56	Sorumuz	C
6K.71.0.000.1014	6K.14 ve 6K.13 için 10-14 A	For 6K.14 and 6K.13, 10-14 A	85.56	Sorumuz	C
6K.71.0.000.1318	6K.14 ve 6K.13 için 13-18 A	For 6K.14 and 6K.13, 13-18 A	85.56	Sorumuz	C
6K.71.0.000.1724	6K.14 ve 6K.13 için 17-24 A	For 6K.14 and 6K.13, 17-24 A	99.61	Sorumuz	C
Not: Farklı gerilim versiyonları için bizimle iletişime geçiniz.		Note: Please contact us for different voltage versions.			
9D Serisi Yüksek Akım Dağıtım Blokları		9D Series High Current Terminal Blocks			
90.01.5.080.0304	Yüksek akım dağıtım bloğu, 80A, 7 bağlantı, 1x(2.5...16mm ²) + 4x(2.5...6mm ²)	High current distribution terminal blocks, 80A, 7 connections, 1x(2.5...16mm ²) + 4x(2.5...6mm ²)	12.46	1	C
90.01.5.125.0206	Yüksek akım dağıtım bloğu, 125A, 8 bağlantı, 1x(10...35mm ²) + 1x(6...16mm ²) + 6x(2.5...16mm ²)	High current distribution terminal blocks, 125A, 8 connections, 1x(10...35mm ²) + 1x(6...16mm ²) + 6x(2.5...16mm ²)	22.25	1	C
90.01.5.175.0310	Yüksek akım dağıtım bloğu, 175A, 12 bağlantı, 2x(10...70mm ²) + 10x(2.5...16mm ²)	High current distribution terminal blocks, 175A, 12 connections, 2x(10...70mm ²) + 10x(2.5...16mm ²)	33.12	1	C
90.01.5.250.0111	Yüksek akım dağıtım bloğu, 250A, 12 bağlantı, 1x(35...120mm ²) + 2x(2.5...35mm ²) + 5x(2.5...16mm ²) + 4x(2.5...10mm ²)	High current distribution terminal blocks, 250A, 12 connections, 1x(35...120mm ²) + 2x(2.5...35mm ²) + 5x(2.5...16mm ²) + 4x(2.5...10mm ²)	53.4	1	C
90.01.5.400.0111	Yüksek akım dağıtım bloğu, 400A, 12 bağlantı, 1x(95...185mm ²) + 2x(2.5...35mm ²) + 5x(2.5...16mm ²) + 4x(2.5...10mm ²)	High current distribution terminal blocks, 400A, 12 connections, 1x(95...185mm ²) + 2x(2.5...35mm ²) + 5x(2.5...16mm ²) + 4x(2.5...10mm ²)	66.74	1	C
7U Serisi Pano Düzleri (DIN Ray Montaj)		7U Series Power Outlets (DIN Rail Mount)			
7U.00.8.230.0010	Gri pano prizi, LED'li	Power outlet for electrical enclosures, grey color, with LED	12.52	5	C
7U.00.8.230.0000	Gri pano prizi	Power outlet for electrical enclosures, grey color	11.58	5	C
7U.00.8.230.0012	Sarı pano prizi, LED'li	Power outlet for electrical enclosures, yellow color, with LED	12.52	5	C
7U.00.8.230.0002	Sarı pano prizi	Power outlet for electrical enclosures, yellow color	11.58	5	C
7D Serisi İzleme Röleleri		7D Series Monitoring Relays			
70.11.8.230.2022	1-faz Dijital/Yüksek gerilim veya pencere modu, 1 CO	1-phase Under/Over voltage or window mode, 1 CO	121.74	5	C
70.31.8.400.2022	3-faz Dijital/Yüksek gerilim veya pencere modu, faz kaybı, faz sırası, 1 CO	3-phase Under/Over voltage or window mode, phase failure, phase rotation, 1 CO	132.24	5	C
70.41.8.400.2030	3-faz Gerilim pencere fonksiyonu, faz kaybı, faz sırası, asimetri, nötr izleme, 1 CO	3-phase Voltage/window mode, phase failure, phase rotation, asymmetry, neutral monitoring, 1 CO	148.14	5	C
70.42.8.400.2032	3-faz Dijital/Yüksek gerilim veya pencere modu, faz kaybı, faz sırası, asimetri, nötr izleme, 2 CO	3-phase Under/Over voltage or window mode, phase failure, phase rotation, asymmetry, neutral monitoring, 2 CO	161.24	5	C
70.61.8.400.0000	3-faz Faz sırası ve faz kaybı izleme rölesi (208...480V)	3-phase Rotation and phase loss monitoring relay (208...480V)	84.45	5	C
70.91.0.000.0002	Termistör (PTC) izleme rölesi, 230VAC/DC, 2 CO	Thermistor (PTC) monitoring relay, 230VAC/DC, 2 CO	98.58	5	C
70.92.8.230.0002	Termistör (PTC) izleme rölesi, 230VAC, 2 CO	Thermistor (PTC) monitoring relay, 230VAC, 2 CO	98.58	5	C
70.51.0.240.2032	Akım izleme rölesi, 50 mA...16A AC/DC, Dijital/Yüksek akım veya pencere modu, 1 CO	Current monitoring relay, 50 mA...16A AC/DC, Under/Over current or Window mode, 1 CO	162.93	5	C
70.51.0.240.2032	Akım izleme rölesi, 50 mA...16A AC/DC, Dijital/Yüksek akım veya pencere modu, NFC ile ayarlanabilir, 1 CO	Current monitoring relay, 50 mA...16A AC/DC, Under/Over current or Window mode, adjustable via NFC, 1 CO	173.78	5	C
Not: Raylı uluşum versiyonları için bizimle iletişime geçiniz.		Note: Please contact us for railway versions			
7F Serisi Pano Havalandırma Filtreleri ve Fanlı-Filtreler		7F Series Panel Ventilation Filters and Fan-Filters			
7F.02.0.000.1000	Havalandırma çöküş filtresi, 92mmx92mm	Exhaust filter, 92mmx92mm	11.2	1	C
7F.20.8.230.1000	Havalandırma fan-filtre, 92mmx92mm, 230VAC, 24m3/h	Fan filter, 92mmx92mm, 230VAC, 24m3/h	66.8	1	C
7F.02.0.000.2000	Havalandırma çöküş filtresi, 125mmx125mm	Exhaust filter, 125mmx125mm	13	1	C
7F.20.8.230.2055	Havalandırma fan-filtre, 125mmx125mm, 230VAC, 35m3/h	Fan filter, 125mmx125mm, 230VAC, 35m3/h	72.6	1	C
7F.02.0.000.4000	Havalandırma çöküş filtresi, 223mmx223mm	Exhaust filter, 223mmx223mm	38.25	1	C
7F.20.8.230.4250	Havalandırma fan-filtre, 223mmx223mm, 230VAC, 250m3/h	Fan filter, 223mmx223mm, 230VAC, 250m3/h	156.51	1	C
7F.02.0.000.3000	Havalandırma çöküş filtresi, 177mmx177mm	Exhaust filter, 177mmx177mm	32.11	1	C
7F.20.8.230.3100	Havalandırma fan-filtre, 177mmx177mm, 230VAC, 100m3/h	Fan filter, 177mmx177mm, 230VAC, 100m3/h	97.51	1	C
Not: Farklı gerilim versiyonları için bizimle iletişime geçiniz.		Note: Please contact us for different voltage versions.			
7H Serisi Pano Isıtıcıları		7H Series Panel Heaters			
7H.51.0.230.0025	Pano ısıtıcı, 25W, 110...230 V AC/DC	Panel Heater, 25W, 110...230 V AC/DC	55.63	1	C
7H.51.0.230.0050	Pano ısıtıcı, 50W, 110...230 V AC/DC	Panel Heater, 50W, 110...230 V AC/DC	76.77	1	C
7H.51.0.230.0100	Pano ısıtıcı, 100W, 110...230 V AC/DC	Panel Heater, 100W, 110...230 V AC/DC	105.72	1	C
7H.51.0.230.0150	Pano ısıtıcı, 150W, 110...230 V AC/DC	Panel Heater, 150W, 110...230 V AC/DC	131.29	1	C
7H.51.0.230.0250	Pano ısıtıcı, 250W, 230 VAC	Panel Heater, 250W, 230 VAC	155.25	1	C
7H.51.8.230.0400	Pano ısıtıcı, 400W, 230 VAC	Panel Heater, 400W, 230 VAC	165.68	1	C
7T Serisi Pano Termostatlar		7T Series Panel Thermostats			
7T.81.0.000.2301	Pano termostatı, NO kontak, -				